

450MT

POWER	
Engine Type	2-cylinder, inline 4-stroke, liquid-cooled, DOHC, 270° crankshaft
Displacement	449.5cc
Bore x Stroke	72×55.2 mm
Max Power	32.5kW(44hp)/8500 rpm
Max Torque	44Nm/6250 rpm
Fuel System	BOSCH EFI
Compression Ratio	11.5:1
Transmission	CF-SC slipper clutch, 6-speed, wet, multi-plate
Throttle Typeaa	Mechanical throttle
CHASSIS/SUSPENSION/BRAKE	
Chassis	Tubular steel frame
Swingarm	Aluminum alloy
Rim	Wire-spoked rims (tubeless)
Front Tire	90/90 R21 CST
Rear Tire	140/70 R18 CST
Front Suspension	KYB, ϕ 41 upside down suspension, compression and damping adjusatble
Rear Suspension	KYB, multi-link rear suspention, preload, compression and rebound adjustable
Front/Rear Suspension Travel	200mm/200 mm
Front Brake	©320mm single disc, four-piston caliper, J.Juan
Rear Brake	©240mm single disc, single-piston caliper, J.Juan
DIMENSIONS & WEIGHT	and the second state and the second state of t
Length x Width x Height	2210 x 870 x (1380mm-1430mm (windshield adjustable))
Wheelbase	1505 mm
Seat Height	820mm / 800mm available by change linkage bolt position
Ground Clearance	220 mm
Fuel Capacity	17.5 L
Weight	175 kg (dry)
ELECTRONICS	
Кеу	Mechanical Key
ABS	BOSCH dual-channel ABS (rear ABS switchable)
Traction Control	BOSCHTCS
Battery	12V 11.2Ah
Headlight	LED
Taillight	LED
Signal Light	LED
Instrument	5-inch curved TFT dislplay, CFMOTO Ride App connectivity
Charging Port	18w USB Type-A & Type-C
T-BOX	Optional Optional
GRAPHIC & TRIM	Zephyr Blue / Tundra Grey



CFMOTO CFMOTO MALAYSIA 1664, Jalan Besar, Taman Iks, 14100 Simpang Ampat, Pulau Pinang Adventure Motorcycle